

RF RF RF RF RF RF RF RF RF RF



RF RF RF RF RF RF RF RF RF RF

•PRODUCT DETAILS•



Weight :	2.8KG/PCS
Material	Zinc alloy/acrylic
Card type	M1 S50 card
Frequency	13.56MHZ
Work Voltage	6V
Alarming Voltage	4.5V
Static Currency	<20uA
Dynamic currency	<200mA
Work temperature	-20-60 degree certigrade
Work humidity	10%-85%RH
Mortise	5 latch security mortise
Unlocking time	Within 1 second
Read distance	2-10mm
Door thickness requirement	35-65mm



## RFID Card to open door

Temic and Mifare card, 100,000 times life, high security, compatible with Energy Saver

## Mechanical keys (2pcs) to open door

Emergency Key to open the door or if you don't want to use RFID cards



## Deadbolt + Anti-card Latch (ANSI Mortise)

Standard 5-bolt electronic cylinder

## Handle

Safe Handle design to protect any break-in attempt and pass 300 thousand times test



## Back Bolt Knob

There is a Bolt knob on the back of the lock, deadbolt latch out to improve your security

## 4x AA Batteries

4 section 6V 5# alkalinity for 10,000 times' unlocking. Low voltage warning, when it is low 4.8V



**00000000**

> 00000 00000 00000 000000000 **RF** 0 0 000000 000 00000 0000 0000 00 0000 00000  
 000000 00 00000 0 00000000000 000 0000 000000 0000000 000 000000 0000000 < ANSI 0  
 .000000 000000 00000 0000 0000000 00000 00000 00 000000 00000 0000 <  
 0 000000 00000 0000000 00000000000 00 00000 0 0000 0000 00000000 000000 0000 <  
 0 0000000 0000000 00000 00000 00000000 0 000000 00 000000 <  
 .000000 0000000000 00 0000 <  
 0 0000000 00000 0 0000000 00000000000 000000000 <  
 0 0000000 0000000 0000000 0000000 0000000 000000000 00000000 0000000 <  
 4 00000000 00 000000 <AA 0000000 00000 0000 1 0000 000 00 00000 0000.