

DH-K809A ABS



1. Jog / Non-Latched

2. 3. 4.

5s 10s 15s



Dimensions	66Lx45Wx30H(mm)
Finished for Shell	Plastic, Abrasion Resistant
Output Contact	NC/NO/COM
Input	12VDC (24VDC by Optional)
Current	8mA
Transmitting Freq	433.92MHZ
Transmitting Power	10mW
Suitable for	access control
Transmitting Distance	≥70m(in open area)
Finished for Shell	Plastic, Abrasion Resistant
Capable	30 Transmitter
Weight	0.2kg

□□□

1.□□□□□□DC10-14V

2.□□□□ <5MA

3.RF□□□□315MHz□433MHZ

4.RF□□□□□□□□□□

5□□□□□□□□ > 90dBm

6.□□□□□□ > 100□□□□□□□□□□

7□□□□□□MCU□□□□□

8.□□□□□□□□□□50□

9□□□□□□□□□□□□□□□□

10.□□□□1CH

1. 5W LED
2. 3W LED
3. 1W LED
4. 0.5W LED

CONTACT US



Sincerely for your service

You are welcome to come to consult

Contact: Yimo Yang
Cellphone/Wechat/Whatsapp: +86 13612936220
Skype: udohow3
Email: udohow1@udohow.com
Web: www.udohow.com

HOME