DH-K809A[illegible]ABS[illegible]

[illegible]/[illegible]

1.Jog / Non-Latched[illegible]/[illegible]“[illegible]/[illegible]”[illegible]

2.[illegible]/[illegible]/[illegible]/[illegible]

3.[illegible]/[illegible]/[illegible]/[illegible]2[illegible]

4[illegible]5s[illegible]10s[illegible]15s[illegible]

Dimensions	66Lx45Wx30H(mm)
Finished for Shell	Plastic, Abrasion Resistant
Output Contact	NC/NO/COM
Input	12VDC (24VDC by Optional)
Current	8mA
Transmitting Freq	433.92MHZ
Transmitting Power	10mW
Suitable for	access control
Transmitting Distance	≥70m(in open area)
Finished for Shell	Plastic, Abrasion Resistant
Capable	30 Transmitter
Weight	0.2kg

□□□
1.□□□□□DC10-14V
2.□□□□ <5MA
3.RF□□□315MHz□433MHZ
4.RF□□□□□□□□□□□
5□□□□□□□> 90dBm
6.□□□□□> 100□□□□□□□□□
7□□□□□□MCU□□□□
8.□□□□□□□□□50□
9□□□□□□□□□□□□□□□□
10.□□□1CH

11.□□□□□□□□□□/□□□□□/□□□□□/□□□□□□□□
12□□□□□□□□□□□□
13.□□□□□DC12V
14.□□□□□10A
15.□□□□□10A 250VAC / 10A 125VAC
10A 30VDC / 10A 28VDC
16.□□□□□□□□□□□
17.□□□3.5cm * 3cm * 1.6cm

□□□□□□□□□□□□□□□□□□□□RKE□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Trunk

Garage door



Braking door

Induction auto doors

Electric telescopic door

□□□

1.Jog□□□LED□□□ LED□

□5□□□□□□□ 3S□□□□LED□□□□□□□□□□□□□□□□□□□□□
2□□□□□□□□□□□□□□□□□2□□□□□□□□□□□□□□□□□□□□□LED□□□□□□□□□□□□□□□□LED□□□□5□□ 3S□□□□LED□□□□□□
3.□□□□□□□□□□□□□□□□□□3□□□□□□□□□□□□□□
4□□□□□□□□□□□□□□□□□□□□□□□□□□□□□5s□10s□15s□□□□□□□□□□