

DH-RF094 It is a keypad RFID contactless access control reader, preclude the use of advanced RF receiver circuit design and embedded micro-controller, combined with efficient decoding algorithms. It has received high sensitivity, current, single DC power supply, low price, high performance characteristics. Dust, moisture, fully sealed design allows users to install the outdoor and other harsh conditions, no mechanical wear and durability.





MATERIAL

HIGH QUALITY PVC MATERIAL
INJECTION MOLDING SHELL

WIRE

WIRING MORE HARDNESS
AND MORE THICK



LOGO AERA

SUPPORT CUSTOM LOGO
PRINTING

SHAPE

STREAMLINED APPEARANCE
DESIGN

INSTALL

SIMPLE DISASSEMBLY
DESIGN

Specifications

Item	Parameters
Operating Voltage	DC 9V-12V ($\pm 5\%$)
Consumed Current	45mA (Standby); 70mA (Working)
Support cards	125KHz, 13.56MHz(Optional)
Read Range	0mm-100mm
Reader interval	<0.5S
Format	Wiegand 26/Wiegand 34
Distance of transmission	WG26/34 ≥ 100 M

Service Temperature	-25°C ~ +75°C
Size	86mm×86mm×18mm
Weight	About 170G
Lead Length	180mm±5mm
Material	ABS & Resin adhesive(waterproof)
Status Indication	Red & Green