

DH-RF094 It is a keypad RFID contactless access control reader, preclude the use of advanced RF receiver circuit design and embedded micro-controller, combined with efficient decoding algorithms. It has received high sensitivity, current, single DC power supply, low price, high performance characteristics. Dust, moisture, fully sealed design allows users to install the outdoor and other harsh conditions, no mechanical wear and durability.





MATERIAL

HIGH QUALITY PVC MATERIAL
INJECTION MOLDING SHELL



WIRE

WIRING MORE HARDNESS
AND MORE THICK



LOGO AERA

SUPPORT CUSTOM LOGO PRINTING

SHAPE

STREAMLINED APPEARANCE DESIGN

INSTALL

SIMPLE DISASSEMBLY DESIGN

Specifications

| Item | Parameters |
|--------------------------|--------------------------------|
| Operating Voltage | DC 9V-12V (±5%) |
| Consumed Current | 45mA (Standby); 70mA (Working) |
| Support cards | 125KHz, 13.56MHz(Optional) |
| Read Range | 0mm-100mm |
| Reader interval | <0.5S |
| Format | Wiegand 26/Wiegand 34 |
| Distance of transmission | WG26/34≥100M |

| | |
|---------------------|----------------------------------|
| Service Temperature | -25°C ~ +75°C |
| Size | 86mm×86mm×18mm |
| Weight | About 170G |
| Lead Length | 180mm±5mm |
| Material | ABS & Resin adhesive(waterproof) |
| Status Indication | Red & Green |