



Funzione:

Chiusura automatica;

B. la velocità di chiusura può essere regolata;

C. alcuni chiudiporta hanno la funzione di restare.

PRODUCT DETAILS SHOW

1 STRETCHABLE MECHANIC ARM

Mechanic Arm can be adjustable, stretchable, even when doorframe and door are not in same plane, it is still able to be installed, satisfying your multiple requirements



2 FASTENED RIVETS

Fastening Rivets assure stability in connection, effective solution in usage and safety, premium performance in wearproof



3 MAIN BODY

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test, Premium & Durable



4 POLE & BEARING

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test, Premium & Durable



Vantaggio:

Il chiudiporta è installato nella parte superiore dell'anta con apertura singola, è applicabile a porte in legno □ porte in acciaio e porte tagliafuoco.

Applicabile a porta singola con larghezza massima della porta di 950 mm e peso della porta di 85-100 kg.

01

CONFIRM TYPE OF DOOR BEFORE INSTALLATION



SUITABLE FOR THESE DOORS

Wooden Door, Aluminum Door, Stainless Steel Door, Iron Door,
Fireproof Door, Anti-Theft Door, Hollow Metal Door etc.

Could be installed on the right or left



Fireproof Door


Wooden Door

Metal Door

Anti-Theft Door


02

ASSURE DOOR AND DOORFRAME ARE ON THE SAME PLANE



DOOR AND DOORFRAME ARE ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe on the same plane, then door closer will work



DOOR AND DOORFRAME ARE NOT ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe on the same plane, then door closer will work