



Function:

A. automatic closing;

B. closing speed can be adjusted;

C. some door closer have the function of staying.

## PRODUCT DETAILS SHOW

### 1 STRETCHABLE MECHANIC ARM

Mechanic Arm can be adjustable,stretchable,even when doorframe and door are not in same plane, it is still able to be installed,satisfying your multiple requirements



### 2 FASTENED RIVETS

Fastening Rivets assure stability in connection, effective solution in usage and safety, premium performance in wearproof



### 3 MAIN BODY

Special Structure Design For Components,Multi-Step Processes For Manufacturing,Pass 100000 Times Test,Premium&Durable



### 4 POLE&BEARING

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test,Premium&Durable



Advantage:

Door closer is installed at the top of the door leaf with single opening, is applicable to wooden door, steel door and fire door.

Applicable to single door with the maximum door width of 950mm and door weight of 35-65kg.

01

## CONFIRM TYPE OF DOOR BEFORE INSTALLATION



### SUITABLE FOR THESE DOORS

Wooden Door, Aluminum Door, Stainless Steel Door, Iron Door,  
Fireproof Door, Anti-Theft Door, Hollow Metal Door etc.  
Could be installed on the right or left



Fireproof Door



Wooden Door




Metal Door



Anti-Theft Door


02

## ASSURE DOOR AND DOORFRAME ARE ON THE SAME PLANE



### DOOR AND DOORFRAME ARE ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe are on the same plane, then door closer will work



### DOOR AND DOORFRAME ARE NOT ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe are on the same plane, then door closer will work