Function:
A.automatic closing;
B.closing speed can be adjusted;
C.some door closer have the function of staying.

PRODUCT DETAILS SHOW

1 STRETCHABLE MECHANIC ARM

Mechanic Arm can be adjustable,stretchable,even when doorframe and door are not in same plane, it is still able to be installed,satisfying your multiple requirements

2 FASTENED RIVETS

Fastening Rivets assure stablity in connection, effective solution in usage and safety, premium performance in wearproof

3 MAIN BODY

Special Structure Design For Components,Multi-Step Processes For Manufacturing,Pass 100000 Times Test,Premium&Durable



4 POLE&BEARING

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test,Premium&Durable

Advantage:
Door closer is installed at the top of the door leaf with single opening, is applicable to wooden door steel door and fire door.
Appliable to single door with the maximum door width of 950mm and door weight of 85-100kg.

01

CONFIRM TYPE OF DOOR BEFORE INSTALLATION

SUITABLE FOR THESE DOORS

Wooden Door,Allumium Door,Stainless Steel Door,Iron Door,
Fireproof Door,Anti-Theft Door,Hollow Metal Door etc.
Could be installed on the right or left

Fireproof Door

Wooden Door

Metal Door

Anti-Theft Door

02

ASSURE DOOR AND DOORFRAME ARE ON THE SAME PLANE





DOOR AND DOORFRAME ARE ON THE SAME PLANE

Whatever you use it on inwarder or outward door,just make sure door and doorframe on the same plane, then door closer will work

DOOR AND DOORFRAME ARE NOT ON THE SAME PLANE

Whatever you use it on inwarder or outward door,just make sure door and doorframe on the same plane, then door closer will work