
DH-2400SL is a kind of **shear lock**. by using the principle of electromagnetic force to attract the armature plate, and then stuck the two fixed legs into the holes on the armature plate. With combination of the power of electromagnetic force and holding force of the fixed legs, the shear lock can create a very large shearing force.






Lock It Twice when there is inappropriate locking,the lock will lock it again,guaranteeing for locking successfully




output

Intelligent circuit Time Delay&Double Signals



Metal-Made Lock Metal-made structure makes it sturdy&durable






Integrated&Miniature Design Integrated and miniature design,making it convenient for installation on any kinds of door frame

Magnetism&Bolt

Adopt electromagnetic force and bolt design,making it reaches 1200kgs holding force,more safer.





Door/Lock Double Signal Contact NO/COM door signal output,NO/NC/ COM lock signal output,satisfy with high-level security requirement in access control



NO (

Durable

Electromagnetism Adopt durable electromagntism design, sucessful 500000 operations(it can work for 5-10 years based on test)



NC

NO 🔴

Technical Parameter:

Model No.: DH-2400SL Holding Force: 2600Lbs(1200kg) Lock: 182L X 30W X 25D(mm) Armature Plate: 182L X 30W X 23.6D(mm) Power supply: DC 12V Operation Current: 850mA Holding Current: 400mA Time Delay: 0/5/10/15sec. LED Red shows locked; Green shows unlocked

Advantage:

For double swing doors: Suitable for 90 or 180 degrees double swing doors;

Relock function: When the lock is unlocked, it will lock the door automatically according to the program.

Smart circuit design: With time delay function, door signal output and lock signal output

All-metal lock body: With integral profiles and precise work, this lock is stronger and more durable.

Ultra durable electromagnetic design: Professional and durable electromagnetic design with over 500,000 times qualified test.

One-piece and small size: One-piece design and small size, which will be easy to install to any kinds of door frame

With both magnetic and latch design: By using electromagnetic force and latch design, the holding force of this shearing lock can achieve up to 1200kg

Armature plate with guide groove: With guide grooves at both sides of the armature plate;

Door/lock status sensor: A set of NO/COM door signal output contact and a set of NO/NC/COM lock signal output contact

CONTACT US





Sincerely for your service

You are welcome to come to consult

Contact: Yimo Yang Cellphone/Wechat/Whatsapp: +86 13612936220 Skype: udohow3 Email: udohow1@udohow.com Web: www.udohow.com

HOME