



Функция:

A. автоматическое закрытие;

B. скорость закрытия может быть скорректирована;

Некоторые дверные доводчики имеют функцию пребывания.

PRODUCT DETAILS SHOW

1 STRETCHABLE MECHANIC ARM

Mechanic Arm can be adjustable, stretchable, even when doorframe and door are not in same plane, it is still able to be installed, satisfying your multiple requirements



2 FASTENED RIVETS

Fastening Rivets assure stability in connection, effective solution in usage and safety, premium performance in wearproof




3 MAIN BODY

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test, Premium & Durable



4 POLE & BEARING

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test, Premium & Durable



Преимущество:

Дверной доводчик устанавливается в верхней части дверного полотна с одним отверстием, применяется для деревянных дверей, стальных дверей и противопожарных дверей.

Применимо к одной двери с максимальной шириной двери 950 мм и весом двери 85-100 кг.

01

CONFIRM TYPE OF DOOR BEFORE INSTALLATION



SUITABLE FOR THESE DOORS

Wooden Door, Aluminum Door, Stainless Steel Door, Iron Door,
Fireproof Door, Anti-Theft Door, Hollow Metal Door etc.

Could be installed on the right or left



Fireproof Door


Wooden Door

Metal Door

Anti-Theft Door


02

ASSURE DOOR AND DOORFRAME ARE ON THE SAME PLANE



DOOR AND DOORFRAME ARE ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe on the same plane, then door closer will work



DOOR AND DOORFRAME ARE NOT ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe on the same plane, then door closer will work